

thinspace



THIN CLIENT RANGE

Thinspace provides a reliable, ecological & cost effective hardware option for your server based computing needs.

The TST200 thin client from Thinspace is one of the most powerful and power efficient entry level thin clients on the market today.

With processing speeds up to 500 MHz and Giga bit LAN as standard, you can easily run the latest Windows applications from a Terminal Server over a LAN/WAN without the need for a PC. The TST200 also has options for internal wireless and a smart card reader.

Overall the TST200 is fast, easy to use and install as well as affordable. An ideal solution for those who want to benefit from utilising the server based computing model. The TST200 represents the best value in the market today.

Remote Management Software

One of the most important features of using thin clients is the ability to manage them effectively. All thin clients from Thinspace can be managed, whether it's a simple configuration to a full machine back up, our management software will allow administrators to manage their enterprise effectively and easily.



Model Shown TST200

Features & Benefits

Low Powered

No Moving Parts

Stylish & Functional

PC Quality Graphics

Can be managed over LAN/WAN

Technical Specifications

	Microsoft CE 6.0	Linux 2.6.24	
System			
Processor	Via Eden 500 MHz	Via Eden 500 MHz	
Chipset	VIA CN896	VIA CN896	
Memory	256 MB DDR2 @667MHZ (up to 2 GB)	512 MB DDR2 @667MHZ (up to 2 GB)	
CF	256 MB (up to 8 GB)	512 MB (up to 8 GB)	
I/O Peripheral			
Rear	1 x VGA (DB 15)	1 x VGA (DB 15)	
	1 x Serial Port (DB-9)	1 x Serial Port (DB-9)	
	1 x RJ-45 Giga LAN	1 x RJ-45 Giga LAN	
	2 x PS/2 Ports	2 x PS/2 Ports	
	2 x USB 2.0 Ports	2 x USB 2.0 Ports	
	Key Lock Slot	Key Lock Slot	
	DC Power Jack	DC Power Jack	
Front	2 x USB 2.0 Ports	2 x USB 2.0 Ports	
	1 x Line-out	1 x Line-out	
	1 x Mic-in	1 x Mic-in	
	Smart Card (opt)	Smart Card (opt)	
Networking			
Ethernet	10/100/1000 RJ-45	10/100/1000 RJ-45	
	2 nd Port (opt)	2 nd Port (opt)	
Wireless	Int. 802.11 b/g (opt)	Int. 802.11 b/g (opt)	
Display			
Interface	DVI & VGA	DVI & VGA	
Max Res.	1600 x 1200 @ 85Hz	1600 x 1200 @ 85Hz	
Communications	RDP 6.0, Citrix ICA 10.04, IE 7	RDP 1.6.0, Citrix ICA 10.60, Firefox 3.0	
Additional Software	PN Agent, Adobe Acrobat reader, Windows Media Player, Go-Global Client.	PN Agent, M Player, Adobe Acrobat reader, Open Office, VNC Viewer, NX Client, Tarantella, SSH Client &RSH, X(XDMCP).	
Environmental			
Power	DC + 12V/40W	DC + 12V/40W	
Operating Temp	0-40° C (21-104° F)	0-40° C (21-104° F)	
Dimensions			
Height	39.9mm	39.9mm	
Depth	150mm	150mm	
Width	209mm	209mm	
Options			
	Smart Card Reader	Smart Card Reader	
	Internal 802.11 b/g	Internal 802.11 b/g	
	VESA Mount Bracket	VESA Mount Bracket	

thinspace Limited

Daresbury Innovation Centre
Keckwick Lane
Daresbury, Cheshire, WA4 4FS

Tel: +44 (0)1925 607 271 **Fax:** +44 (0)1925 607 275

email: info@thinspace.co.uk

www.thinspace.co.uk