

# thinspace



## THIN CLIENT RANGE

Thinspace provides a reliable, ecological & cost effective hardware option for your server based computing needs.

The TST600 thin client from Thinspace is the fastest, and most power efficient thin client on the market today.

With processing speeds up to 1.5 GHz, Giga bit LAN & DVI as standard, you can easily run the latest Windows applications from a Terminal Server over a LAN/WAN without the need for a PC. The TST600 also has options for internal wireless and a smart card reader. Overall the TST600 is fast, easy to use and install as well as affordable. With XP Embedded, you also have the option of running applications locally. An ideal solution for those who want to benefit from utilising the server based computing model. The TST600 represents the best value in the market today.



**Model Shown TST600**

## Remote Management Software

One of the most important features of using thin clients is the ability to manage them effectively. All thin clients from Thinspace can be managed, whether it's a simple configuration to a full machine back up, our management software will allow administrators to manage their enterprise effectively and easily.

### Features & Benefits

- Low Powered
- No Moving Parts
- Stylish & Functional
- PC Quality Graphics
- Can be managed over LAN/WAN

## Technical Specifications

	Microsoft CE 6.0	Linux 2.6.24	XP Embedded SP2
System			
Processor	Via Eden C7 1.5 GHz	Via Eden C7 1.5 GHz	Via Eden C7 1.5 GHz
Chipset	VIA CN896	VIA CN896	VIA CN896
Memory	256 MB DDR2 @667MHZ (up to 2 GB)	512 MB DDR2 @667MHZ (up to 2 GB)	512 MB DDR2 @667MHZ (up to 2 GB)
CF	256 MB (up to 8 GB)	512 MB (up to 8 GB)	512 MB (up to 8 GB)
I/O Peripheral			
Rear	1 x VGA (DB 15)	1 x VGA (DB 15)	1 x VGA (DB 15)
	1 x DVI	1 x DVI	1 x DVI
	1 x RJ-45 Giga LAN	1 x RJ-45 Giga LAN	1 x RJ-45 Giga LAN
	2 x PS/2 Ports	2 x PS/2 Ports	2 x PS/2 Ports
	2 x USB 2.0 Ports	2 x USB 2.0 Ports	2 x USB 2.0 Ports
	Key Lock Slot	Key Lock Slot	Key Lock Slot
	DC Power Jack	DC Power Jack	DC Power Jack
Front	2 x USB 2.0 Ports	2 x USB 2.0 Ports	2 x USB 2.0 Ports
	1 x Line-out	1 x Line-out	1 x Line-out
	1 x Mic-in	1 x Mic-in	1 x Mic-in
	Smart Card (opt)	Smart Card (opt)	Smart Card (opt)
Networking			
Ethernet	10/100/1000 RJ-45	10/100/1000 RJ-45	10/100/1000 RJ-45
	2 <sup>nd</sup> Port (opt)	2 <sup>nd</sup> Port (opt)	2 <sup>nd</sup> Port (opt)
Wireless	Int. 802.11 b/g (opt)	Int. 802.11 b/g (opt)	Int. 802.11 b/g (opt)
Display			
Interface	DVI & VGA	DVI & VGA	DVI & VGA
Max Res.	1600 x 1200 @ 85Hz	1600 x 1200 @ 85Hz	1600 x 1200 @ 85Hz
Communications	RDP 6.0, Citrix ICA 10.04, IE 7	RDP 1.6.0, Citrix ICA 10.60, Firefox 3.0	RDP 6.0, Citrix ICA 10.150, IE 7
Additional Software	PN Agent, Adobe Acrobat reader, Windows Media Player, Go-Global Client.	PN Agent, M Player, Adobe Acrobat reader, Open Office, VNC Viewer, NX Client, Tarantella, SSH Client &RSH, X(XDMCP).	Windows Media player 11, Web PN Agent, Adobe Acrobat reader, Flash ver. 9.0.115, Shockwave Player ver. 10.3 Java ver. 1.4.2_16,
Environmental			
Power	DC + 12V/40W	DC + 12V/40W	DC + 12V/40W
Operating Temp	0-40° C (21-104° F)	0-40° C (21-104° F)	0-40° C (21-104° F)
Dimensions			
Height	39.9mm	39.9mm	39.9mm
Depth	150mm	150mm	150mm
Width	209mm	209mm	209mm
Options			
	Smart Card Reader	Smart Card Reader	Smart Card Reader
	Internal 802.11 b/g	Internal 802.11 b/g	Internal 802.11 b/g
	VESA Mount Bracket	VESA Mount Bracket	VESA Mount Bracket

### thinspace Limited

Daresbury Innovation Centre  
Keckwick Lane  
Daresbury, Cheshire, WA4 4FS

**Tel:** +44 (0)1925 607 271 **Fax:** +44 (0)1925 607 275

**email:** info@thinspace.co.uk

**www.thinspace.co.uk**